

## WHAT IS CLAIMED IS:

- Sub  
All
1. A seat cushion comprising:  
 a pair of generally flat pads for supporting a  
 5 user's buttocks;  
 a handle disposed between the pads for carrying  
 said seat cushion;  
 arms, interconnecting the pads and said handle,  
 for holding the pads in a spaced apart relationship and  
 10 enabling grasping of said handle by the user, said arms  
 being flexible for enabling the pads to be oriented in  
 both a planar relationship for supporting the user's  
 buttocks and a coplanar relationship for enabling transport  
 of said seat cushion by the handle.
- 15
2. The seat cushion according to claim 1 wherein  
 said handle and said arms are recessed from a top of each  
 of the pads for enabling the user's coccyx to depend  
 between the pads in order to prevent pressure on the  
 20 coccyx.
3. The seat cushion according to claim 2 wherein the  
 pads, arms and handle are integrally molded.
- 25
4. The seat cushion according to claim 3 wherein  
 said arms include forearms and aftarm each joined to  
 opposite ends of said handle.
- 30
5. The seat cushion according to claim 4 wherein  
 each of the pads include an arcuate forward perimeters, the  
~~forward perimeters been joined by the forearms,~~

10073370-020502

Sub B1  
6. The seat cushion according to claim 5, wherein each of the pads include an arcuate rearward perimeter, the rearward perimeter being joined by the aftarms.

Sub A12 5  
7. The seat cushion according to claim 2 further comprising means for releasably holding the pads in the coplanar relationship.

8. A seat cushion comprising:  
10 a pair of generally flat pads for supporting a user's buttocks, the pads having minor image perimeters;  
a handle disposed between the pads for carrying said seat cushion;  
arms, interconnecting the pads and said handle,  
15 for holding the pads in a spaced apart relationship and enabling grasping of said handle by the user, the arms being flexible for enabling the pads to be oriented in both a planar relationship for supporting the user's buttocks and a coplanar relationship for enabling transport of said  
20 seat cushion by the handle.

9. The seat cushion according to claim 8, wherein said handle and arms have a thickness smaller than a thickness of the pads and are disposed between the pads for  
25 enabling the user's coccyx to depend between the pads in ~~order to prevent pressure on the coccyx.~~

Sub B1  
10. The seat cushion according to claim 9 wherein the handle arms and pads each have a bottom surface disposed in  
30 a single plane with the pads oriented for supporting the user's buttocks.

Sub  
A13

11. The seat cushion according to claim 10 wherein the pads, arms and handle are integrally molded.

12. The seat cushion according to claim 11 wherein 5 said arms include forearms and aftarms each joined to opposite ends of said handle.

13. The seat cushion according to claim 12 wherein each of the pads include an arcuate forward perimeters, the 10 forward perimeters being joined by the forearms.

14. The seat cushion according to claim 13 wherein each of the pads include an arcuate rearward perimeter, the rearward perimeter being joined by the aftarms.

15

15. A seat cushion comprising:

a pair of generally flat pad for supporting a user's buttocks;

20 a web, interconnecting the pads, for holding the pads in a spaced apart relationship, said web being flexible for enabling the pads to be oriented in both a planar relationship for supporting the user's buttocks and a coplanar relationship for enabling transport of said seat cushion; and

25 a handle attached to said web for carrying the pads in the coplanar relationship.

16. The seat cushion according to claim 15 wherein said web and handle are recessed from a top of each of the 30 pads for enabling the user's coccyx to depend between the pads in order to prevent pressure on the coccyx.

10000370-020502

17. The seat cushion according to claim 16 wherein the pads, web and handle are integrally molded.

18. The seat cushion according to claim 16 wherein  
5 said handle is separately attached to said web.

19. The seat cushion according to claim 18 wherein each of the pads include an arcuate forward perimeter, the forward perimeters being joined by said web.  
10

20. The seat cushion according to claim 19 wherein each of the pads include an arcuate rearward perimeter, the rearward perimeter being joined by said web.  
15

21. The seat cushion according to claims 19 wherein said web comprises a pair of forearms attached to one end of said handle and a pair of aftarms attached to another end of said handle.

22. The seat cushion according to claim 21 further comprising a non-slip surface disposed on a bottom side of each pad.  
20

23. The seat cushion according to claim 16 further  
25 comprising means for releasably holding the pads in the coplanar relationship.